20

WHAT IS CLAIMED IS:

first and second interlockable fastener tracks configurable in an interlocked, closed position and an unlocked open position;

a slider movable along said fastener tracks to configure said tracks in said interlocked position so as to close said opening and to configure said fastener tracks in said unlocked position so as to allow access through said opening to said package interior;

said fastener tracks having opposed ends

15 located adjacent said opposed sides of said front and
said rear panels;

stops adjacent said ends of said fastener tracks to interfere with and prevent travel of said slider beyond said fastener tracks;

a side seal of pre-selected width joining together one side of said front and said rear panels;

a shroud covering said slider and at least the major portion of said fastener tracks;

weakening portions extending adjacent said

25 fastener tracks for severing of said shroud in
preparation for removal of said shroud from the remainder
of said reclosable flexible package; and
said shroud defining at least one opening for said
slider, said opening having an acute angle portion

30 communicating with said weakening portion.

2. The reclosable flexible package of claim 1 wherein said weakening portion includes a line of weakness extending along at least the portion of said fastener tracks.

- 3. The reclosable flexible package of claim 2 wherein said line of weakness extends along the substantial entirety of said fastener tracks.
- 4. The reclosable flexible package of claim 2 wherein said line of weakness extends across substantially the entire extent of said reclosable flexible package.
- 5. The reclosable flexible package of claim 1 wherein said weakening portion includes a tear-start feature formed in one side of said reclosable flexible package to initiate tearing of said reclosable flexible package.
- 6. The reclosable flexible package of claim 5 further comprising a line of weakness extending along said fastener tracks, cooperating with said tear-start feature to tear said reclosable flexible package, allowing said shroud to be removed from the remainder of said reclosable flexible package.
- 7. The reclosable flexible package of claim 6 further comprising an angled weakening line between said tear-start feature and said line of weakness.
- 8. The reclosable flexible package of claim 7 wherein the said angled severing line crosses said 25 fastener tracks.
 - 9. The reclosable flexible package of claim 8 wherein the said line is a generally straight line.
- 10. The reclosable flexible package of claim 7 wherein said opening through which said slider protrudes,
 said opening connecting said angled severing line and said line of weakness.

- 11. The reclosable flexible package of claim 1 wherein said shroud includes an upper portion comprising a fin seal.
- 12. The reclosable flexible package of claim
 11 wherein said shroud further includes a side fin seal
 above said fastener tracks, in line with the side seal
 trunning said front and said rear panels.
- 13. The reclosable flexible package of claim 1 wherein said shroud is integrally formed with said front and said rear panels, comprising monolithic portions of said front and said rear panels.
 - 14. The reclosable flexible package of claim 1 wherein said shroud includes shroud panels separately formed and joined to said front and said rear panels.
- 15. The reclosable flexible package of claim 1 wherein said side seal having an enlarged end portion of enlarged width adjacent said fastener tracks, with at least a part of said enlarged end portion disposed below said fastener tracks; and
- wherein said enlarged end portion is disposed beneath the substantial entirety of said slider and shields said slider, deflecting product being discharged from said package interior, around said slider.
- 16. The reclosable flexible package of claim 1
 25 further comprising a peelable seal preventing
 communication of said opening with said package interior.
 - 17. The reclosable flexible package of claim 16 wherein said peelable seal comprises a hermetic seal.
- 18. The reclosable flexible package of claim 1 wherein said stops comprise deformed end portions of said fastener track.

- 19. The reclosable flexible package of claim 18 wherein said fastener track end portions are softened with application of ultrasonically generated heat and deformed under pressure.
- 5 20. The reclosable flexible package of claim 19 wherein the bottoms of said fastener tracks are preserved undeformed.